

PACKING MACHINE F28C



FEATURES

- Angular inline packaging machine
- Profile construction allows flexible design
- Uses flat film (PE,PP,composite)
- Controlled film unwind
- Automatic sealing temperature control
- Air cooling systems
- Mechanical and electrical safety systems
- Optimal accessibility for service and fault finding (Swing out of the longitudinal sealing)
- Siemens S7 PLC Control
- Clear operating station with coloured touchpanel
- Optimal operator-leading through enter-key masks and online-help
- Fault indication by clear text and indicator lamps
- Structured access-rights for machine-parameters through password-levels
- Synchronisation for additional machines prepared

TECHNICAL DATA

Cycling Speed:	up to max. 60 bags / min.
Bag width:	up to 280 mm / 450 mm
Bag length:	infinitely variable (mm)
Passage clearance:	90 mm / 180 mm
Film thickness:	approx. 40 bis 150 my
Electrical supply:	230 VAC / 50 Hz
Power Requirements:	max. 12 A
Compressed Air:	min. 6 bar
Dimensions:	approx. 1500x1200x1700 mm
Weight:	approx. 150 kg

OPTIONS

- Thermotransfer-direct printer
- Ethernet port for data communication
- Labeller
- Linked bag chains
- Easy bag opening system
- Protection slider for sealing station
- Slider or flap in the filling tube
- Longitudinal- and transverse perforation
- Air hole punch
- Euro hole punch
- Hand feed table
- Other options on request
- Data base