

PACKING MACHINE PAXMATIC H28 / 45 / 65



FEATURES

- Compact, vertical, in line bagging machine, with lateral filling tube
- Profile construction allows flexible design
- Uses polyethylene - folded film
- Bag separation by means of two step knife
- Automatic sealing temperature control
- Air cooling sealing system
- Simple operator console with ClearText message centre
- Pack counter
- Controlled film unwind
- Fault indication by ClearText and indicator lamps
- Mechanical and electrical safety systems
- Optimal accessibility for service and fault finding

TECHNICAL DATA

Cycling Speed:	up to max.40 bags / min.
Bag Width:	50 up to 280/450/650 mm *
Bag Length:	Infinitely variable (mm)
Passage Clearance:	90/150 mm *
Film Thickness:	approx. 40 to 120 my
Electrical Supply:	230 VAC / 50 Hz
Power Requirements:	max. 12 A
Compressed Air:	approx. 150 NL / min.4.5 bar
Dimensions:	approx.1400x800x2000mm (LxWxH) *
Weight:	approx. 150 kg*

* depending on the model

OPTIONS

- Horizontal infeed unit for oriented packaging
- Folding module for laminated film
- Thermotransfer - direct printer
- Labeller
- Linked bag chains
- Easy bag opening systems
- Additional machines, counting machines
- Infeed conveyors:
 - Collators, bucket and pocket conveyors
- Outfeed conveyor
- Check weigher
- Other options on request