

PACKING MACHINE PAXMATIC F28 ULTRASONIC



FEATURES

- Compact, vertical, in line packaging machine
- Profile construction allows flexible design
- Ultrasonic transversal sealing
- Uses flat film (PE,PP,composite)
- Controlled film unwind
- Automatic sealing temperature control
- Air cooling systems
- Mechanical and electrical safety systems
- Optimal accessibility for service and fault finding (Swing out of the longitudinal sealing)
- Siemens S7-300 steering gear
- Ethernet port for data communication
- Clear operating station with coloured touchpanel
- Optimal operator-leading through enter-key masks and online-help
- Fault indication by clear text and indicator lamps
- Structured access-rights for machine parameters through password-levels
- Data base
- Synchronisation for additional machines prepared

TECHNICAL DATA

Cycling Speed:	up to 50 bags / min.
Bag Width:	up to 280 mm
Bag Length:	max. 240 mm
Film Thickness:	approx. 40 to 120 my
Electrical Supply:	3 x 400 VAC / 50 Hz
Power Requirements:	max. 16 A
Compressed Air:	min. 6 bar
Dimensions:	approx. 2000x1500x1700mm
Weight:	approx. 450 kg

OPTIONS

- Thermotransfer - direct printer
- Labeller
- Print mark scanner
- Exchangable unit for the thermic sealing
- Bagopener support
- Slider or flap in the filling tube
- Air hole punch
- Euro hole punch
- Bag clamp
- Other options on request