

PACKING MACHINE PAXMATIC W22



MERKMALE

- Compact, vertical, inline packaging machine
- Profile construction allows flexible design
- Uses folded film (PE, PP, composite)
- Controlled film unwind
- Automatic sealing temperature control
- Air cooling systems
- Mechanical and electrical safety systems
- Optimal accessibility for service and fault finding (Swing out of the longitudinal sealing)
- Siemens S7-300 steering gear
- Ethernet port for data communication
- Optimal operator-leading through enter-key masks and online-help
- Fault indication by clear text and indicator lamps
- Structured access-rights for machine-parameters through password-levels
- Data base
- Synchronisation for additional machines prepared

TECHNICAL DATA

Cycling Speed:	up to 50 bags / min.
Bag Width:	up to 280 mm
Bag Length:	Infinitely variable (mm)
Passage Clearance:	90 mm
Film Thickness:	approx. 40 to 120 my
Electrical Supply:	230 VAC / 50 Hz
Power Requirements:	max. 12 A
Compressed Air:	approx. 150 NL / min.4.5 bar
Dimensions:	approx.1100x750x1150mm
Weight:	approx. 150 kg

OPTIONS

- Thermotransfer-direct printer
- Labeller
- Linked bag chains
- Easy bag opening system
- Bagopener support
- Slider or flap in the filling tube
- Vongitudinal- and transverse perforation
- Air hole punch
- Euro hole punch
- MiniGrip
- Folded modules for flat film
- Hand feed table
- Other options on request